

# LongHorn FLO K9

Go With the Flow.  
LongHorn FLO K9.

**EASY TO  
CLEAN**



**SEAMLESS**



**SHOCK  
ABSORBING**

*A non-porous flooring with seamless uniformity and fatigue-reducing properties, LongHorn FLO K9 is a safe and comfortable surface that is easy to maintain. With a high content of recycled materials, LongHorn FLO K9 is an attractive and sustainable canine surfacing.*

*With a durable wear layer that can be recoated indefinitely, anti-bacterial, anti-microbial LongHorn FLO K9 is the optimal surfacing solution for your commercial canine application. Available in a variety of colours, thicknesses and densities.*



**EASY TO INSTALL OVER MOST EXISTING SURFACES,  
 FIELD-APPLIED LAYERS OF SELF-LEVELLING  
 LIQUID POLYURETHANE ARE Poured OVER  
 A RESILIENT RUBBER BASEMAT FOR A  
 BEAUTIFULLY SEAMLESS SURFACE**

**LONGHORN FLO K9 SPECIFICATIONS**

**PHYSICAL PROPERTIES**

SURFACE HARDNESS	81 SHORE A	
COATING	WATER-BASED TOP COATS	
SHOCK ABSORPTION		
(STANDARD BASEMAT)		
7MM BASEMAT	EN1408	28.3%
9MM BASEMAT	EN1408	32.0%
COEFFICIENT OF FRICTION	0.56 DRY/0.28 WET	
IMPACT RESISTANCE	EN1517	>800GR @ 10°C
RESISTANCE TO INDENTATION	EN1516	0.32MM @ 5 MIN
RESISTANCE TO ROLLING LOADS	EN1569	>1500 N
STATIC LOAD LIMIT	225 PSI	
TENSILE STRENGTH	DIN53455	3071 PSI (21N/MM <sup>2</sup> )
ELONGATION AT BREAK	DIN53455	200%
TEAR STRENGTH	DIN53515	294 PLI (51N/MM)

**NOTE:** PHYSICAL PROPERTIES CAN VARY BY PRODUCT TYPE.  
 INFORMATION ABOVE APPLIES TO THIS PRODUCT ONLY.

**INDOOR PAD & POUR SURFACE COLOURS AVAILABLE**

